

EINSCHRAUBBARE MESSING SPRITZDÜSEN

Auch mit abgewinkelter Öffnung zum optimalen Zielen.

Material: Messing

Max. Druck: 33 bar

Max. Bearbeitungs – Temperatur: 150° C



Thread "E"	Orifice Dia. "d"	L	A	"C" Hex	Pkg Qty
M3.5 x .6	.062	.42	.14	3/16	5
M3.5 x .6	.086	.42	.14	3/16	5
M4 x .7	.062	.54	.18	3/16	5
M4 x .7	.086	.54	.18	3/16	5
M5 x .8	.062	.63	.21	1/4	5
M5 x .8	.086	.63	.21	1/4	5
M5 x .8	.117	.63	.21	1/4	5
M6 x 1.0	.062	.63	.21	1/4	5
M6 x 1.0	.086	.63	.21	1/4	5
M6 x 1.0	.117	.63	.21	1/4	5
M6 x 1.0	.150	.63	.21	1/4	5
M8 x 1.25	.062	.80	.30	3/8	5
M8 x 1.25	.086	.80	.30	3/8	5
M8 x 1.25	.117	.80	.30	3/8	5
M8 x 1.25	.160	.80	.30	3/8	5
M8 x 1.25	.220	.80	.30	3/8	5
1/8-NPT/BSPT	.062	.90	.37	1/2	5
1/8-NPT/BSPT	.086	.90	.37	1/2	5
1/8-NPT/BSPT	.117	.90	.37	1/2	5
1/8-NPT/BSPT	.160	.90	.37	1/2	5
1/8-NPT/BSPT	.220	.90	.37	1/2	5
1/8-NPT/BSPT	.280	.90	.37	1/2	5
M3.5 x .6	.062	.32	.14	3/16	5
M4 x .7	.062	.36	.18	3/16	5
M5 x .8	.086	.42	.21	1/4	5
M6 x 1.0	.086	.42	.21	1/4	5
M6 x 1.0	.117	.42	.21	1/4	5

