


788E 787E 791E 797E



Größe 65

Art.-Nr.	D	L	Ausf. d. Bohrung			maximale Bohrung			Steigung
			LQ	Q	G	○	◊	□	
788 E SK 65	99,5	58			*	4 - 7 mm			0,5
788 E SK 65	99,5	58		*		8 - 10 mm			0,5
788 E SK 65	99,5	58	*			11 - 65 mm			0,5
788 E SK 65	99,5	58		*			7 - 56 mm	7 - 46 mm	1,0
787 E SK 65 G	99,5	53			*	4 - 65 mm			0,5
787 E SK 65 W	99,5	53			*	6, 20, 40 mm			

Größe 80

Art.-Nr.	D	L	Ausf. d. Bohrung			maximale Bohrung			Steigung
			LQ	Q	G	○	◊	□	
791 E SK 80	114,5	53			*	5 - 7 mm			1,0
791 E SK 80	114,5	53		*		8 - 10 mm			1,0
791 E SK 80	114,5	53	*			11 - 80 mm			1,0
791 E SK 80	114,5	53		*			8 - 68 mm	8 - 56 mm	1,0
791 E SK 80 G	114,5	53			*	5 - 80 mm			1,0
791 E SK 80 W	114,5	53			*	20, 40, 80 mm			

Größe 100

Art.-Nr.	D	L	Ausf. d. Bohrung			maximale Bohrung			Steigung
			LQ	Q	G	○	◊	□	
797 E SK 100	144,5	59	*			42 - 100 mm			1,0
797 E SK 100	144,5	59		*			50 - 88 mm	50 - 70 mm	1,0
797 E SK 100 G	144,5	59			*	42 - 100 mm			1,0
797 E SK 100 W	144,5	59			*	45, 65, 90 mm			